



BLSL840

Light Duty Slider

The **BLSL840** with its ultra-quiet high torque brushless DC motor is the first choice for Residential/Commercial applications. This full features state of the art operator uses a 120/220VAC single phase main power source and utilizes a high efficient switching power supply to supply the proper voltage for operation. The operator is equipped with a built-in 24VDC battery backup system and it can operate with a direct solar panel connection as well.

This operator is designed to operate in any climate; it does not require a gearbox or a battery heater to operate in -20°F. Temperature between -20°F and -40°F require a battery heater and below -40°F it requires a gearbox heater as well.



The optional chain routing under the sprocket for extra chain clearance for non-raised pad mounting

These unique engineering innovations backed by the safety and reliability of the most advanced control board in the industry ensure a smooth operation for any Platinum Access Systems' operator.

Specification	Data		
Speed Control:	This operator can control the speed on uphill downhill gate. It keeps the speed constant.	Dimension:	22" x 13" x 23" H
Manual Release:	Back Drivable Optional Fail Safety	Main Power:	120/220 VAC Single Phase On/Off Switch
Gate Capacity:	Maximum Gate Weight 800 lbs. Maximum Gate Length 40ft. 12" per second		Built-in 24V DC Battery Backup (7 ampHr 12V DC x 2)
Mechanical:	Gear Reducer Size 70	Compliance:	ETL Listed UL325/UL991
Motor:	Brushless Continuous Duty Instant Reversing 24V DC	Warranty:	Brushless Motor: 10yrs. 8yrs. Parts: 8yrs. 6yrs.









BLSL840 Light Duty Slider

FEATURES AND BENEFITS:

- Dynamic Speed Control No speed variation when gate load changes and power switches between AC and battery. Slider works on slope without coasting.
- Automatic Learning With Self Sync Automatically synchronizes gates with different travel times for primary/secondary gate installation.
- Solar Priority Power Supply With a larger solar panel, the gate will run on the solar panel instead of the batteries when the sun light is sufficient, saving battery life.
- Soft Start and Soft Stop Minimizes wear on the gate system that significantly helps the gate last longer.
- High Efficiency Brushless Motor For smooth, high torque and maintenance free operation.
- Solid State Motor Drivers For quiet and long lasting operation
- Advanced Maglock Control Engage maglock before or after gate is closed.
 Maglock works at both gate open and close position.
- Dual Output Loop Detector Rack Type "B" relays on loop detector can be used for additional features.
- Individual Alarm For Primary/Secondary Installation Alarm sounds from individual operator, automatically indicates the obstructed gate.

- Motor Brake and Maglock Release by FIRE/KEY Input – Enables manual gate operation in emergency.
- One Controlled Power Supply Output for Photo Beam Detector – In solar installation, turns off PBD when the gate is closed to save battery life.
- High Capacity DC Back Up Over 100 cycles on DC back up depending on models and gate sizes.
- Adjustable Leaf Delay Delay on either leaf from the primary unit.
- Stackable Limit Switches For additional features.
- Fail Safe/Secure Capability Be able to set to fail secure, fail safe or open on power fail.
- Heavy Duty Chassis Corrosion resistant powder coated chassis.
- BLGOC-2200 control board with input/output LED's.
- Electronic reversing sensor built into control board.
- Adjustable timer from 0-60 seconds.
- Surge protection.
- Alarm reset button.
- Weatherproof polyethylene.

PLATINUM ACCESS SYSTEMS, INC.

1725 E. Grevillea Court, Ontario, CA 91761 I **Sales**: (909) 259-6005 I **Fax**: (909) 923-7890 I www.platinumasi.com **Technical Support** (909) 259-6001 I **Email**: sales@platinumasi.com I techsupport@platinumasi.com



