



27 SERIES

SMART KEYPAD AND CARD READER SYSTEMS

FEATURES

- Bluetooth connectivity
- 2 Wiegand inputs*
- Control up to 2 gates/doors
- App-based programming and management
- SBI Flex™ 64-bit and standard 26-bit protocol

MODELS

- · 27-210 Edge E1 Smart Keypad
- · 27-220 Edge E2 Smart Card Reader
- · 27-230 Edge E3 Smart Keypad / Card Reader
- 27-240 Edge E4 Smart Weather-resistant Controller
 Edge E1 and E2 available with optional intercom
 Edge E2 and E3 available with HID or Secura Key card reader



* Number of Wiegand inputs available dependent on model



GET THE EDGE SMART KEYPAD APP





POWERFULLY SIMPLE APP

All programming and management can be done quickly and securely via the app.

SBI FLEX 64-BIT PROTOCOL

Our proprietary Wiegand protocol allows for 4- to 11-digit keypad codes with 3-digit facility code for maximum flexibility.

DUAL 365-DAY TIMERS

A separate 365-day timer on each relay gives you the versatility and control you need.

CONFIGURABLE USER PERMISSIONS

Set specific user permissions on all keypad codes, transmitters, card readers, and long-range tag readers independently.







SPECIFICATIONS

PHYSICAL

Dimensions 6.21"(H) x 7.44"(W) x 5.25"(D) (27-240 only) 8.97"(H) x 7.09"(W) x 2.44"(D) Shipping Weight 8 lbs. (27-240 only) 5 lbs.

ELECTRICAL

Input 12–24 VAC/DC

12-VDC transformer included (PS-12DC1)

less than 60 mA @ 24 VDC

Current Draw less than 111 mA @ 12 VDC

with one relay latched and LED components on

RELAY

Contact Rating 10 A @ 120 VAC / 24 VDC

COMMUNICATION

Connection Bluetooth

ENVIRONMENTAL

Operating Temperature -15 to 158 °F

▲ Actual voltage should be no more than 10% beyond specified range. Use of the included 12-VDC transformer is recommended.

CONTROL IT YOUR WAY



APP[†]



KEYPAD



WIEGAND DEVICES


† Administrator only

CONNECTIVITY



BLUETOOTH





Model 27-210 shown

AVAILABLE MODELS (SEE PRICE GUIDE TO SEE ALL MODELS)



EDGE E1
Keypad
27-210



EDGE E2 Card Reader 27-220



EDGE E3
Keypad / Card Reader
27-230



EDGE E4
Weather-resistant Controller
27-240

For more information, visit us online:

securitybrandsinc.com

