



PLATINUM ACCESS SYSTEMS, INC.

BLSW2212**Heavy Duty Commercial and Industrial Swinger**

The **BLSW2212** with its ultra-quiet high torque brushless DC motor is the first choice for Residential/Commercial applications. This full features state of the art operator uses the power source with the highest voltage for Operational Voltage. A 120/220VAC single phase main power source utilizes a step-down transformer to supply the proper voltage for operation. The operator is equipped with a built-in 24VDC battery backup system and it can operate with a direct solar panel connection as well.

This operator is designed to operate in any climate; it does not require a gearbox or a battery heater to operate in -20°F. Temperature between -20°F and -40°F require a battery heater and below -40°F it requires a gearbox heater as well.

These unique engineering innovations backed by the safety and reliability of the most advanced control board in the industry ensure a smooth operation for any Platinum Access Systems' operator.



Specification	Data		
Speed Control:	This operator can control the speed on uphill downhill gate. It keeps the speed constant.	Dimension:	22" x 13" x 23" H
Manual Release:	Back Drivable Optional Fail Safety	Main Power:	120/220 VAC Single Phase On/Off Switch Built-in 24V DC Battery Backup (33AH 12V DC x 2)
Gate Capacity:	Maximum Gate Weight: Length: 1300 lbs. 20' 2200 lbs. 12' 90° Opening in 13-18 Seconds (Max @ 120°)		
Mechanical:	Gear Reducer Size 80	Compliance:	ETL Listed UL325/UL991
Motor:	Brushless Continuous Duty Instant Reversing 24V DC	Warranty:	Residential Commercial Brushless Motor: 10yrs. 8yrs. Parts: 8yrs. 6yrs.



PLATINUM ACCESS SYSTEMS, INC.

BLSW2212

Heavy Duty Commercial and Industrial Swinger

FEATURES AND BENEFITS:

- | | |
|---|---|
| <ul style="list-style-type: none"> • Dynamic Speed Control – No speed variation when gate load changes and power switches between AC and battery. Slider works on slope without coasting. • Automatic Learning With Self Sync – Automatically synchronizes gates with different travel times for primary/secondary gate installation. • Solar Priority Power Supply – With a larger solar panel, the gate will run on the solar panel instead of the batteries when the sun light is sufficient, saving battery life. • Soft Start and Soft Stop – Minimizes wear on the gate system that significantly helps the gate last longer. • High Efficiency Brushless Motor – For smooth, high torque and maintenance free operation. • Solid State Motor Drivers – For quiet and long lasting operation • Advanced Maglock Control – Engage maglock before or after gate is closed. Maglock works at both gate open and close position. • Dual Output Loop Detector Rack – Type “B” relays on loop detector can be used for additional features. • Individual Alarm For Primary/Secondary Installation – Alarm sounds from individual operator, automatically indicates the obstructed gate. | <ul style="list-style-type: none"> • Motor Brake and Maglock Release by FIRE/KEY Input – Enables manual gate operation in emergency. • One Controlled Power Supply Output for Photo Beam Detector – In solar installation, turns off PBD when the gate is closed to save battery life. • High Capacity DC Back Up – Over 100 cycles on DC back up depending on models and gate sizes. • Adjustable Leaf Delay – Delay on either leaf from the primary unit. • Stackable Limit Switches – For additional features. • Fail Safe/Secure Capability – Be able to set to fail secure, fail safe or open on power fail. • Heavy Duty Chassis – Corrosion resistant powder coated chassis. • BLGOC-2000 control board with input/output LED's. • Electronic reversing sensor built into control board. • Adjustable timer from 0-60 seconds. • Surge protection. • Alarm reset button. • Weatherproof polyethylene clam shell cover. |
|---|---|

PLATINUM ACCESS SYSTEMS, INC.

1725 E. Grevillea Court, Ontario, CA 91761 I Sales: (909) 259-6005 I Fax: (909) 923-7890 I www.platinumasi.comTechnical Support (909) 259-6001 I Email: sales@platinumasi.com I techsupport@platinumasi.com